

Industrial Stationary

AIR COMPRESSORS Jenny®



Base Plate Mounted Compressors

Standard Features

- Heavy-duty single or two stage cast iron compressor pump
Made in Somerset, PA USA
- Splash lubricated
- Belt driven with a large flywheel for extra cooling and easier start-up
- Oil sight glass
- Each unit is filled with Jenny Ultimate Blue Compressor Pump Oil
- Directional air shroud for reduced pump temperatures
- Totally enclosed heavy-duty belt guard



F34A-B



K15A-B

Single Stage

| Model | Pump | HP | Power Supply | 125 PSI | | |
|--------|------|-------|--|----------|----------|-----------|
| | | | | Pump RPM | CFM Disp | Del'd Air |
| F12A-B | F | 1/2 | 115 Volt (through 2 HP) or 230 Volt 1 Phase | 680 | 3.4 | 2.2 |
| F34A-B | | 3/4 | | 1080 | 5.4 | 3.1 |
| K1A-B | | 1 | | 560 | 6.4 | 4.0 |
| K15A-B | K | 1-1/2 | 208, 230, 460 or 575 Volt 3 Phase | 870 | 9.9 | 6.2 |
| K2A-B | | 2 | | 1140 | 13.0 | 8.0 |
| G2A-B | G | 3 | 208, 230, 460 or 575 Volt 3 Phase | 480 | 13.0 | 9.1 |
| G3A-B | | | | 770 | 20.8 | 14.0 |
| G5A-B | | | | 1020 | 27.5 | 17.8 |
| J5A-B | J | 5 | | 780 | 28.8 | 23.0 |

Electric

- Auto Start/Stop control with pressure unloader set at 105-125 PSI (single stage) or 145-175 PSI (two stage)
- Control group (not mounted)
- Check valve
- Magnetic starter is included on all 5 HP and larger units
- Industrial/Commercial grade UL Listed electric motor
- Thermal overload motor protection

Two Stage

| Model | Pump | HP | Power Supply | 175 PSI | | |
|--------|------|-------|--|----------|----------|-----------|
| | | | | Pump RPM | CFM Disp | Del'd Air |
| GT2B-B | GT | 2 | 115 Volt (through 2 HP) or 230 Volt 1 Phase | 450 | 9.1 | 7.1 |
| GT3B-B | | 3 | | 660 | 13.4 | 10.7 |
| W3B-B | W | 5 | 208, 230, 460 or 575 Volt 3 Phase | 480 | 13.4 | 10.7 |
| GT5B-B | GT | | | 900 | 18.2 | 15.2 |
| W5B-B | W | 7-1/2 | 208, 230, 460 or 575 Volt 3 Phase | 760 | 21.0 | 17.5 |
| U75B-B | U | | | 610 | 37.5 | 27.2 |
| U10B-B | T | 10 | 208, 230, 460 or 575 Volt 3 Phase Only | 710 | 43.7 | 35.2 |
| T15B-B | | 15 | | 520 | 71.5 | 56.5 |
| T20B-B | | 20 | | 670 | 92.1 | 72.2 |
| T25B-B | | 25 | | 780 | 107.2 | 83.0 |



G3A-B



W5B-B

Options

- Constant run control
- Dual control
- Magnetic starter
- Air line filter
- Lubricator
- Aftercooler
- Dryer
- Other pressures available upon request



Base Plate Mounted Compressors

- Powder coated, extra heavy steel base plate
- Large canister intake filter with replaceable filter elements
- Pressure relief safety valve
- Pressure gauge
- Oil sight glass



K5HGA-B



T25KGB-B

Gas

- Constant run control set at 105-125 PSI (single stage) or 145-175 PSI (two stage)
- High quality pilot valve
- Pneumatic throttle idle control
- Honda GX Series OHV Engine or Kohler OHV V-Twin Engine



GT11HGB-B

Single Stage

| Model | Pump | HP | Drive | Pump RPM | CFM Disp | Del'd Air |
|----------|------|-----|----------------|----------|----------|-----------|
| K5HGA-B | K | 5.5 | Recoil Start | 1250 | 14.2 | 8.6 |
| C6HGA-B | C | 6.5 | | 1250 | 17.0 | 10.3 |
| G9HGA-B | G | 9 | | 890 | 24.0 | 15.6 |
| G11HGA-B | | 11 | 1060 | 28.6 | 18.3 | |
| J11HGA-B | J | 13 | Electric Start | 860 | 31.8 | 22.9 |
| J13HGA-B | | | | 980 | 37.6 | 27.1 |

125 PSI

Two Stage

| Model | Pump | HP | Drive | Pump RPM | CFM Disp | Del'd Air |
|-----------|------|----|----------------|----------|----------|-----------|
| GT9HGB-B | GT | 9 | Recoil Start | 950 | 19.2 | 15.4 |
| GT11HGB-B | | 11 | | 1030 | 20.8 | 16.3 |
| W11HGB-B | W | 13 | Electric Start | 760 | 21.0 | 17.6 |
| W13HGB-B | | | | 900 | 24.8 | 20.8 |
| U18KGB-B | | | | 800 | 49.2 | 34.7 |
| T25KGB-B | T | 25 | | 625 | 85.9 | 66.5 |

175 PSI

Options

Air line filter ■ Lubricator ■ Electric start
 Other pressures available upon request
 Other engine options available upon request

UL and CSA are not required for gas engine units.

Electric Stationary Compressors

Standard Features

- Heavy-duty single or two stage cast iron compressor pump
Made in Somerset, PA USA
- Splash lubricated
- Oil sight glass
- Belt driven with a large flywheel for extra cooling and easier start-up
- Each unit is filled with Jenny Ultimate Blue Compressor Pump Oil
- Directional air shroud for reduced pump temperatures
- Totally enclosed heavy-duty belt guard
- Tank gauge
- Tanks are powder coated and ASME certified
- 60 gallon tanks and larger are ASME National Board certified
- Protectively mounted fittings
- Manual tank drain(s)
- Large canister intake filter with replaceable filter elements
- Special unloading valves to assist in motor starting
- Pressure relief safety valve



F13A-17



K15A-30



G3A-60V



K15A-30V

Single Stage

| Model | Pump | HP | Tank Gallon | Power Supply | 125 PSI | | | |
|---------|------|-------|-------------|---|-----------------------------------|----------|-----------|------|
| | | | | | Pump RPM | CFM Disp | Del'd Air | |
| F12A-17 | F | 1/2 | 17 | 115 Volt (through 2 HP) or 230 Volt 1 Phase | 680 | 3.4 | 2.2 | |
| F34A-17 | | 3/4 | | | 1080 | 5.4 | 3.1 | |
| F34A-30 | | 1 | 560 | | 6.4 | 4.0 | | |
| K1A-30 | K | 1-1/2 | 60 | | 870 | 9.8 | 6.2 | |
| K15A-30 | | 30 | 1140 | | 13.1 | 8.0 | | |
| K2A-30 | | 60 | 480 | | 13.1 | 9.1 | | |
| K2A-60 | G | 2 | 30 | | 208, 230, 460 or 575 Volt 3 Phase | 770 | 20.8 | 14.0 |
| G2A-30 | | | 60 | | | 1020 | 27.5 | 17.8 |
| G2A-60 | | | 80 | | | 780 | 28.8 | 23.0 |
| G3A-30 | J | 5 | 60 | | | | | |
| G3A-60 | | | 80 | | | | | |
| G5A-60 | | | 80 | | | | | |
| G5A-80 | J | 5 | 60 | | | | | |
| J5A-60 | | | 80 | | | | | |
| J5A-80 | | | | | | | | |

Options

- Constant run ■ Dual control ■ Low oil level switch
- Automatic tank drain ■ Magnetic starter
- Control circuit transformer ■ Vertical tank
- Air line filter ■ Lubricator
- Aftercooler ■ Dryer
- Other pressures and tank sizes available upon request



Air Compressors
E483335

Electric Stationary Compressors

- Auto Start/Stop control with pressure unloader set at 105-125 PSI (single stage) or 145-175 PSI (two stage)
- Magnetic starter is included on all 5HP and larger units
- Industrial/Commercial grade UL Listed electric motor
- Thermal overload motor protection
- Alternator and magnetic starter are standard on all duplex models



U10B-120

GT5B-80V



Two Stage

| Model | Pump | HP | Tank Gallon | Power Supply | 175 PSI Pump RPM | CFM Disp | Del'd Air | | | | | |
|----------|------|-------|-------------|---|--|--|--|--|--|------|-------|------|
| GT2B-60 | GT | 2 | 60 | 115 Volt (through 2 HP) or 230 Volt 1 Phase | 450 | 9.1 | 7.1 | | | | | |
| GT2B-80 | | | 80 | | 660 | 13.4 | 10.7 | | | | | |
| GT3B-60 | W | 3 | 60 | | 208, 230, 460 or 575 Volt 3 Phase | 440 | 13.4 | 10.7 | | | | |
| GT3B-80 | | | 80 | | | 660 | 13.4 | 10.7 | | | | |
| W3B-60 | GT | 5 | 60 | | | 208, 230, 460 or 575 Volt 3 Phase Only | 900 | 18.2 | 15.2 | | | |
| W3B-80 | | | 80 | | | | 900 | 18.2 | 15.2 | | | |
| GT5B-60 | W | 5 | 60 | | | | 208, 230, 460 or 575 Volt 3 Phase Only | 760 | 21.0 | 17.5 | | |
| GT5B-80 | | | 80 | | | | | 760 | 21.0 | 17.5 | | |
| GT5B-120 | U | 7-1/2 | 120 | | | | | 208, 230, 460 or 575 Volt 3 Phase Only | 610 | 37.5 | 27.2 | |
| W5B-60 | | | 60 | | | | | | 610 | 37.5 | 27.2 | |
| W5B-80 | U | 10 | 80 | | | | | | 208, 230, 460 or 575 Volt 3 Phase Only | 710 | 43.7 | 35.2 |
| W5B-120 | | | 120 | | | | | | | 710 | 43.7 | 35.2 |
| U75B-80 | T | 15 | 80 | 208, 230, 460 or 575 Volt 3 Phase Only | | | | | | 520 | 71.5 | 56.5 |
| U75B-120 | | | 120 | | | | | | | 520 | 71.5 | 56.5 |
| U10B-80 | T | 20 | 80 | | 208, 230, 460 or 575 Volt 3 Phase Only | | | | | 670 | 92.1 | 72.2 |
| U10B-120 | | | 120 | | | | | | | 670 | 92.1 | 72.2 |
| T15B-120 | T | 25 | 120 | | | 208, 230, 460 or 575 Volt 3 Phase Only | | | | 780 | 107.0 | 83.0 |
| T15B-240 | | | 240 | | | | | | | 780 | 107.0 | 83.0 |
| T20B-120 | T | 20 | 120 | | | | 208, 230, 460 or 575 Volt 3 Phase Only | | | 670 | 92.1 | 72.2 |
| T20B-240 | | | 240 | | | | | | | 670 | 92.1 | 72.2 |
| T25B-120 | T | 25 | 120 | | | | | 208, 230, 460 or 575 Volt 3 Phase Only | | 780 | 107.0 | 83.0 |
| T25B-240 | | | 240 | | | | | | | 780 | 107.0 | 83.0 |

Duplex Single Stage

| Model | Pump | HP | Tank Gallon | Power Supply | 125 PSI Pump RPM | CFM Disp | Del'd Air |
|------------|------|----|-------------|--|---------------------|----------|-----------|
| 2(K15A)-60 | K | 3 | 60 | 115 Volt (through 2 HP) 230 Volt 1 Phase | 870 | 19.8 | 12.4 |
| 2(G5A)-80 | G | 10 | 80 | | 1020 | 55.0 | 35.6 |
| 2(J5A)-120 | J | | 120 | | 780 | 57.6 | 46.0 |

Two Stage

| Model | Pump | HP | Tank Gallon | Power Supply | 175 PSI Pump RPM | CFM Disp | Del'd Air |
|-------------|------|----|-------------|--|---------------------|----------|-----------|
| 2(GT5B)-120 | GT | 10 | 120 | 208, 230, 460 or 575 Volt 3 Phase | 900 | 36.6 | 30.4 |
| 2(W5B)-120 | W | | | | 760 | 42.0 | 35.0 |
| 2(U10B)-120 | U | 20 | 240 | 208, 230, 460 or 575 Volt 3 Phase Only | 710 | 87.2 | 70.4 |
| 2(U10B)-240 | | | | | 780 | 214.0 | 166.0 |



T25B-240

W5B-80



UL US Air Compressors LISTED E483335

Climate Control Compressors

Standard Features

- Heavy-duty cast iron compressor pump
Made in Somerset, PA USA
- Splash lubricated
- Belt driven with a large flywheel for extra cooling and easier start-up
- Each unit is filled with Jenny Ultimate Blue Compressor Pump Oil
- Directional air shroud for reduced pump temperatures
- Totally enclosed heavy-duty belt guard
- Tanks are powder coated and ASME certified
- 60 gallon tanks and larger are ASME National Board certified
- Oil sight glass
- Protectively mounted fittings
- Manual tank drain(s)
- Large canister intake filter with replaceable filter elements
- Special unloading valves to assist in motor starting
- Tank gauge
- Pressure relief safety valve
- Auto Start/Stop control with pressure unloader set at 75-100 PSI
- Magnetic starter is included on all 5HP and larger units
- Industrial/Commercial grade UL Listed electric motor
- Thermal overload motor protection
- Alternator and magnetic starter standard on all duplex models

Simplex Single Stage

| Model | Pump | HP | Tank Gallon | Power Supply | 100 PSI Pump RPM | CFM Disp | Del'd Air |
|-----------|------|-------|-------------|---|---------------------|----------|-----------|
| F12C-30C | F | 1/2 | 30 | 115 Volt (through 2 HP) 230 Volt 1 Phase | 590 | 2.9 | 1.7 |
| K1C-30C | K | 1 | | | 520 | 5.9 | 3.7 |
| K15C-30C | | 1.5 | | | 660 | 7.9 | 5.1 |
| Two Stage | | | | 208, 230 460, or 575 Volt 3 Phase | 100 PSI | | |
| GT2C-60C | GT | 2 | 60 | | 540 | 11.0 | 9.1 |
| W3C-80C | W | 3 | 80 | | 481 | 13.5 | 11.6 |
| W5C-80C | | 5 | | | 760 | 21.5 | 17.7 |
| U75C-80C | U | 7-1/2 | 120 | | 610 | 38.0 | 28.5 |
| U10C-80C | | 10 | | | 710 | 43.6 | 35.2 |
| T15C-120C | T | 15 | 120 | | 520 | 72.4 | 57.5 |
| T20C-120C | | 20 | | | 670 | 92.6 | 73.5 |
| T25C-120C | | 25 | | 780 | 107.0 | 85.0 | |

Duplex Single Stage

| Model | Pump | HP | Tank Gallon | Power Supply | 100 PSI Pump RPM | CFM Disp | Del'd Air |
|--------------|------|----|-------------|---|---------------------|----------|-----------|
| 2(F12C)-30C | F | 1 | 30 | 115 Volt (through 2 HP) 230 Volt 1 Phase | 590 | 5.8 | 3.4 |
| 2(K1C)-60C | K | 2 | 60 | | 520 | 11.8 | 7.4 |
| 2(K15C)-60C | | 3 | 660 | | 15.8 | 10.2 | |
| Two Stage | | | | 208, 230 460, or 575 Volt 3 Phase | 100 PSI | | |
| 2(GT15C)-60C | GT | 3 | 60 | | 410 | 16.8 | 13.8 |
| 2(GT2C)-60C | | 4 | 540 | | 22.0 | 18.2 | |
| 2(W3C)-80C | W | 6 | 80 | | 480 | 27.0 | 23.2 |
| 2(W5C)-80C | | 10 | 760 | | 43.0 | 35.4 | |
| 2(U75C)-120C | U | 15 | 120 | | 610 | 76.0 | 57.0 |
| 2(U10C)-120C | | 20 | 710 | | 87.2 | 70.4 | |
| 2(T15C)-240C | T | 30 | 240 | | 520 | 145.0 | 115.0 |
| 2(T20C)-240C | | 40 | | 670 | 185.0 | 147.0 | |
| 2(T25C)-240C | | 50 | | 780 | 214.0 | 170.0 | |

K1C-30C



W5C-80C



2GT2C-60C

Options

- Low oil level switch ■ Automatic tank drain ■ ASME National Board tank
- Magnetic starter ■ Control circuit transformer ■ Vertical Tank
- Air line filter ■ Lubricator ■ Aftercooler ■ Dryer



Air Compressors
E483335

Fire Sprinkler Stationary Compressors

Base Plate Mounted

Standard Features

- Heavy-duty single stage cast iron compressor pump
Made in Somerset, PA USA
- Splash lubricated
- Belt driven with a large flywheel for extra cooling and easier start-up
- Each unit is filled with Jenny Ultimate Blue Compressor Pump Oil

- Directional air shroud for reduced pump temperatures
- Totally enclosed heavy-duty belt guard
- Powder coated, extra heavy steel base plate
- Large canister intake filter with replaceable filter elements
- Magnetic starter is included on all 5HP and larger units
- Industrial/Commercial grade UL Listed electric motor
- Thermal overload motor protection
- Oil sight glass



Base Mounted System Size

Maximum Gallons in system to be pumped to 40 PSI in 30 Minutes

| Model | Pump | HP | Power Supply | Pump RPM | CFM del'd @ 40 PSI | Optional Auto Control Group |
|-------|---------|-----|---|----------|--------------------|-----------------------------|
| 220 | F13S-BS | 1/3 | 115 Volt (through 2 HP) or 230 Volt 1 Phase | 670 | 3.3 | ACGF |
| 290 | F12S-BS | 1/2 | | 950 | 3.8 | |
| 350 | F34S-BS | 3/4 | | 1200 | 4.4 | |
| 425 | K34S-BS | K | 208, 230, 460 or 575 Volt 3 Phase | 520 | 5.3 | ACGK |
| 480 | F1S-BS | F | | 1 | 1430 | 6.0 |
| 600 | K1S-BS | K | 1-1/2 | 790 | 7.4 | ACGK |
| 885 | K15S-BS | | | 2 | 1140 | |
| 985 | K2S-BS | G | 3 | 1280 | 12.4 | ACGD |
| 1215 | G2S-BS | | | 630 | 15.1 | |
| 1775 | G3S-BS | | | 950 | 21.8 | |
| 1950 | G5S-BS | J | 5 | 1030 | 24.2 | ACGJ |
| 2115 | J5S-BS | | | 830 | 26.0 | |

Tank Mounted/30 Gallon

| Model | Pump | HP | Power Supply | Pump RPM | CFM del'd @ 40 PSI | Optional Auto Control Group |
|-------|----------|-----|--|----------|--------------------|-----------------------------|
| 220 | F13S-30S | 1/3 | 115 Volt (through 2 HP) 230 Volt 1 Phase | 670 | 3.3 | ACGF |
| 290 | F12S-30S | 1/2 | | 950 | 3.8 | |
| 350 | F34S-30S | 3/4 | | 1200 | 4.4 | |
| 425 | K34S-30S | K | 208, 230, 460 or 575 Volt 3 Phase | 520 | 5.3 | ACGK |
| 480 | F1S-30S | F | | 1 | 1430 | |
| 600 | K1S-30S | K | 1-1/2 | 790 | 7.4 | ACGK |
| 885 | K15S-30S | | | 2 | 1140 | |
| 985 | K2S-30S | G | 3 | 1280 | 12.4 | ACGD |
| 1215 | G2S-30S | | | 630 | 15.1 | |
| 1775 | G3S-30S | | | 950 | 21.8 | |
| 1950 | G5S-30S | J | 5 | 1030 | 24.2 | ACGJ |
| 2115 | J5S-30S | | | 830 | 26.0 | |

Tank Mounted

Additional Standard Features

- Tanks are powder coated and ASME certified
- Protectively mounted fittings
- Manual tank drain(s)
- Large canister intake filter with replaceable filter elements
- Special unloading valves to assist in motor starting
- Tank gauge
- Pressure relief safety valve
- Auto Start/Stop control with pressure unloader set at 30-40 PSI

Options

- ASME National Board tank
- Magnetic starter
- 17 gallon tank
- Vertical tank
- Low oil level switch
- Automatic tank drain
- Air line filter
- Aftercooler
- Dryer
- Control Group



F12S-30S



G5S-30S



K15S-30S





J AIR COMPRESSORS Jenny®

Jenny Products, Inc.
850 North Pleasant Avenue
Somerset, PA 15501-1069
Phone 814-445-3400
Fax 814-445-2280
www.jennyproductsinc.com
www.jennycompressor.com