

Hand Carry

Standard Features

- Lightweight, compact and extremely portable
- Single stage, direct coupled, oil lubricated pump
- Cast iron cylinder for extended pump life
- Aluminum head for better heat dissipation
- Each unit is filled with Jenny Synthetic Blue Compressor Pump Oil
- Canister inlet filter with replaceable filter elements
- Forced ventilation cooling system
- Powder coated heavy duty steel tank and frame assembly
- Protectively mounted fittings
- Anti-vibration feet
- Air line regulator and two gauges for line and tank pressure
- Pressure relief safety valve
- Manual tank drain(s)
- Special unloading valves to assist in motor/engine starting



AM840-4HG-HC4V



AM780-HC2

AM780-HC4V

Electric Units

- Start/Stop pressure switch control set at 105-125 PSI
- On/Off Switch
- Thermal overload motor protection with manual reset
- 6 ft power cord

Model	HP	Tank Gallon	Drive	CFM @ 100 PSI	CFM @ 125 PSI
AM780-HC2	2	1.5	115 Volt	4.1	3.6
AM780-HC4V		4			
AM780-HC4H		6			
AM780-HC6V		6			
AM840-4HG-HC4V	4	4	Gas/Honda	4.7	4.4



AM780-HC6V

AM780-HC4H

Gasoline Engine

- High quality pilot valve
- Pneumatic throttle idle control
- Constant run control set at 105-125 PSI
- Recoil start Honda GX Series OHV Engine